

Kite-5200 Series

MOBILE WIRELESS GATEWAY WITH 5G AND WI-FI 5



DESCRIPTION

SYSTEM ARCHITECTURE	Octa-Core CPU T2081, 1800 MHz 4 GB RAM, 256 MB Flash optional M2. PCIe SSD up to 960 GB
POWER SUPPLY	24 to 110 VDC, wide-range power supply (compliant to EN 50155)
AMBIENT TEMPERATURE	depending on temperature class of Wi-Fi module Class OT4, -40.. +70 °C (85 °C) operating or Class OT3, -25.. +70 °C (85 °C) operating -40.. +85 °C storage
STANDARDS	EN 50155

STANDARD CONFIGURATIONS

ORDER NO.	MODEL	LAN 1 (M12 X-CODED)	LAN 2 (M12 X-CODED)	5G	WI-FI 802.11AC 3X3 MIMO	GNSS	USB 2.0 / RS232 (M12 8-PIN A-CODED)	BYPASS RELAYS	ANTENNA CONNECTORS	IP CLASS
3633-52101	Kite-5210 EU	1 Gbit	1 Gbit	●●	●●	●	●	●	15x QLS	IP40
3633-52301	Kite-5230 EU	1 Gbit	1 Gbit	●●●	-	●	●	●	13x QLS	IP40
Further information on www.westermo.com										

Westermo Eltec GmbH
Galileo-Galilei-Str. 11
55129 Mainz
Germany

Phone +49 6131 918 100
Email info.eltec@westermo.com
www westermo.com

Copyright © 2025 by Westermo Eltec GmbH, Mainz.
All trademarks are the property of their owners. All rights reserved.

Revision: 1.0 | Date: 18.09.2026