

CYBOX LTE 2

RAILWAY ROUTER WITH LTE CAT-6 AND WI-FI 5

ELTEC systems

WESTERMO

DESCRIPTION

System Architecture	Dual-Core CPU T1023, 1200 MHz 1 GB RAM, 128 MB Flash
Power Supply	24 to 110 VDC, wide-range power supply (compliant to EN 50155)
Ambient Temperature	depending on temperature class of Wi-Fi module Class OT4, -40.. +70 °C (85 °C) operating or Class OT3, -25.. +70 °C (85 °C) operating -40.. +85 °C storage
Standards	EN 50155

STANDARD CONFIGURATIONS

ORDER NO.	MODEL	LAN 1 (M12 X-coded)	LAN 2 (M12 X-coded)	Ethernet Switch	LTE Cat-6	Wi-Fi 802.11ac 3x3 MIMO	Input PSU 24 – 110 VDC (M12 A-coded)	Input PoE on LAN 1	USB 2.0/RS232 (M12 8-pin A-coded)	GNSS	Bypass Relays	Antenna Connectors	Antenna Combiners	IP Class
3201-0000	CYLTE-1050V0	1 Gbit	1 Gbit	-	●	●	●	●	●	●	-	6x QLS	-	IP40
3201-0010	CYLTE-1051V0	1 Gbit	1 Gbit	-	●	-	●	●	●	●	-	3x QLS	-	IP40
3201-0020	CYLTE-1052V0	1 Gbit	1 Gbit	-	●●	-	●	●	●	●	-	5x QLS	-	IP40
3201-0030	CYLTE-1055V0	1 Gbit	1 Gbit	-	●	-	●	●	●	●	-	3x SMA	-	IP40
3201-0040	CYLTE-1062V0	1 Gbit	1 Gbit	●	●●	-	●	-	●	●●	●	6x QLS	-	IP40

Further information on www.westermo.com and www.eltec.com

Westermo Network Technologies AB FON +46 16 42 80 00
Metallverksgatan 6 FAX +46 16 42 80 01
72130 Västerås EMAIL info@westermo.com
Sweden WWW westermo.com

Copyright © 2021 by ELTEC Elektronik AG, Mainz.
All trademarks are the property of their owners. All rights reserved.

Revision: 1.1 | Date: 31.03.2022